



T Series

TR1 G-Build Engine

TR1

Power range: 5.5–7.4 kW; 7.4–9.9 bhp
Fixed speeds: 1500, 1800 r/min

Reliable, durable single-cylinder air-cooled G-Build diesel engines

Special Attributes

- ✓ suitable for generating sets
- ✓ designed for continuous operation in ambient temperatures up to 52°C (122°F)
- ✓ oil cooling by means of air flow over deep crankcase finning

Basic Engine Characteristics

- diesel fuelled
- direct injection
- single cylinder
- air cooled
- naturally aspirated
- electric start (hand start optional)

Design Features and Equipment

- medium duty air cleaner*
- inlet and exhaust manifolds
- fuel injection pump and self-vent fuel system
- fuel filter
- fuel lift pump*
- self-regulating plunger type lubricating oil pump
- spin-on lubricating oil filter
- decompressor lever
- flywheel with cooling fan
- SAE 4 flywheel housing
- mechanical governing
- 12V starter motor*
- safety switches*
- fuel control solenoid (energised to run)*
- standard skid base packing
- 250 hour service intervals
- operators' handbook



Emissions

Complies with EU Stage 3A emissions regulations.

Optional Items

- 12V battery charge alternator

See also items with asterisk under *Design Features and Equipment*.

A range of options allows you to select a specification that matches your requirements; please consult your Lister Petter distributor.

Warranty


- standard: two years from delivery
 - optional: five year limited warranty
- Conditions apply.

* Optional items standard on most builds.

T Series: TR1 Engine Technical Data Sheet

Power Outputs			
Power	r/min	1500	1800
Continuous	kW	5.5	6.7
	bhp	7.4	9.0
Intermittent (Fuel Stop)	kW	6.1	7.4
	bhp	8.2	9.9

Approximate Dimensions and Weight ¹		
Dry weight	kg	133
	lb	337
Length (A): no fuel tank	mm	698
	in	17.5
Width (B)	mm	444
	in	20.51
Height (C)	mm	683
	in	26.88



Rating Definitions, to ISO 3046

ISO Standard Conditions

Barometric pressure 100 kPa
Relative humidity 30%
Ambient temperature at air inlet manifold 25°C

Fixed speed power: continuous power (ICN)

The power in kW which the engine is capable of delivering continuously at the stated crankshaft speed, under ISO standard conditions, measured at the flywheel without power-absorbing accessories, provided that the engine is overhauled and maintained in good operating condition and that fuel to BS EN 590 Class A1 or A2, and lubricating oils to the correct performance specification and viscosity classification as recommended by Lister Petter Limited, are used.

Fixed speed power: overload power (ICXN)

The maximum power in kW which the engine is capable of delivering intermittently at the stated crankshaft speed for a period not exceeding one hour in any period of twelve hours' continuous running, immediately after working at the continuous power, under ISO standard conditions and with the provisions specified for continuous power above.

De-rating

For non-standard site conditions, reference should be made to relevant BS, ISO and DIN standards.

Notes: 1. Power ratings measured at the flywheel apply to a fully run-in, non derated engine without power absorbing accessories or transmission equipment. 2. The overload capability applies to a fully run-in engine. This is normally attained after a running period of about 50 hours. 3. Excluding radiator.

Technical Data		
Type of fuel injection		Direct
Number of cylinders		1
Aspiration		Natural
Direction of rotation looking on flywheel end		Anticlockwise
Nominal cylinder bore	mm	98.42
	in	3.875
Stroke	mm	101.6
	in	4.0
Total cylinder capacity	litre	0.773
	in ³	47.17
Compression ratio		15.5:1
Minimum idling speed	r/min	850
Number of flywheel ring gear teeth		110
Crankshaft end thrust (maximum continuous)	kgf	132
	lbf	290
Crankcase vacuum (minimum)	mbar	2.0
	in H ₂ O	0.8
Crankcase vacuum (average)	mbar	3.5
	in H ₂ O	1.4
Lubricating oil pressure (mean) with the oil at 110°C (230°F)	bar	2.0
	lbf ft ²	29

Distributor's Address



UK

Lister Petter Limited, Dursley, Gloucestershire
GL11 4HS England

Tel: +44 (0)1453 544141; fax: +44 (0)1453 546732

E-mail: sales@lister-petter.co.uk <http://www.lister-petter.co.uk>

USA

Lister Petter Americas Inc. 815 E. 56 Highway, Olathe, Kansas 66061 USA

Tel: +1 913 764-3512; fax: +1 913 764-5493

E-mail: info@lister-petter.com; <http://www.lister-petter.com>

France

Lister Petter France, 9 Avenue de l'Escouvrier, Zone d'Activités,
95842 Sarcelles Cedex, France; tel: +33 (0)1 39330420

Fax: +33 (0)1 34195760; email: commercial@lister-petter-france.fr

India

Lister Petter India (P) Ltd, 32/2/5/1, Kondhawa (BK), Pune 411048 India

Tel: +91 20 2693 2688/3644/3645; fax: +91 20 2693 3286

Email: smith@listerpetterindia.com

China

Lister Petter China, Jinan Fuqiang Power Co. Ltd, Shandong Zhangqiu Industrial
Area, Jinan 250220, P.R. China

Tel: +86 531 8558 4852; fax: +86 531 8558 4820

Lister Petter have made efforts to ensure that the information in this data sheet is accurate but reserve the right to amend specifications and information without notice and without obligation or liability.